

MODEL 34 BAG-IN-BOX FILLER

APPLICATIONS: General Films provides high-quality all stainless steel fillers for ice cream mix and bulk fluid milk, water, and hot fill products. Our fillers are trouble free, low maintenance equipment that exceed all sanitary requirements.

DESCRIPTION: The Model 34 features +/-0.3% fill accuracy by flow meter with consistency of product pressure. The cabinet is NEMA 4 construction. The filler includes a programmable controller, auto start, decap, recap, and eject. General Films' fillers offer adjustability to permit bag size changes in seconds – from one through six gallon bags. The Model 34 can fill 3 to 4 five gallon bags per minute depending on product supply and is CIP capable. General Films provides a selection of standard layouts or we can customize the tables and frames to match the needs of your dairy.

SPECIFICATIONS:

Power	120V - 5AMP
Compressed air	60PSI @ 1CFM
Dimensions	33" wide, 36" deep, 65" high
Shipping weight	300 pounds

Flow Rates	Flow Meter Size	Comments
1.5 - 15 Gal/Min	3/4"	Lab Size
6.5 - 65 Gal/Min	1"	Standard
17.5 - 175 Gal/Min	1-1/2"	High Flow

AVAILABILITY: Our fillers are custom manufactured for each application. We can typically build and install the equipment for your operation within 6 - 8 weeks.



The information contained herein is based upon data believed to be reliable and relates only to the matters specifically contained herein. Although such information is, to the best of our knowledge and belief, accurate and reliable as of the date hereof, no representation, warranty (express or implied, or merchantability, fitness or otherwise), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information. It is the user's responsibility to satisfy itself as to the suitability, accuracy, reliability and completeness of such information for its particular use. There is no warranty against patent infringement and General Films not be liable for any loss, damage, or injury that may occur from the use of this information. No statement herein shall be construed as an endorsement of any product or process.